

RS6 & RS10

Rainscreen



The unique, three dimensional matrix provides a continuous space for drainage and drying — eliminating the threat of trapped moisture.

- Eliminates the deteriorating effect of mold and rot between siding and sheathing
- Reduces the chances of premature peeling or blistering of finishes
- Prevents damage from surfactants by separating the cladding from water resistive barrier
- Saves time and labor costs by eliminating the need for furring strips
- Fabric serves as “sacrificial layer” in stone or stucco applications, while preventing mortar from blocking drainage and drying capacity



	RS6	RS10
THICKNESS (SIZE OF GAP)	.25 in (6 mm)	.40 in (10 mm)
WIDTH	39.37 in (1 m)	39.37 in (1 m)
LENGTH PER ROLL	100 ft (30.48 m)	61.5 ft (18.75 m)
COVERAGE PER ROLL	325 sq ft (30.19 m ²)	200 sq ft (18.58 m ²)
ROLLS PER PALLET	8 rolls	8 rolls
MAX. UV EXPOSURE	90 days	
COMPOSITION	Polypropylene	

**BENJAMIN
OBDYKE**
roof & wall products

Benjamin Obdyke Incorporated
400 Babylon Road, Suite A
Horsham, PA 19044
1.800.523.5261